




PREMIUM FREE ROLLING POSITION TRAILER

Code	Size	LI / SR	PR	T.D.	RIM	O.D.	S.W.	S.L.R.	L.C.C.		
									32nds	in.	in.
S8245351	11R22.5	144/142 L	14	14	8.25	41.3	10.9	19.2	6175	5840	105
S8245358	11R24.5	146/143 M	14	14	8.25	43.2	10.9	20.2	6610	6005	105
S8245385	255/70R22.5	140/137 L	16	14	7.50	36.5	9.7	17.0	5510	5070	120
S8245375	295/75R22.5	144/141 M	14	14	8.25	39.8	10.8	18.6	6175	5675	110
S8245378	285/75R24.5	144/141 M	14	14	8.25	41.1	10.8	19.3	6175	5675	110



The S622 is a premium free-rolling position trailer tire. With a decoupling groove that resists irregular sidewall wear, and wide ribs to prevent damage caused by high-scrub applications, the S622 is also a low-rolling resistance tire designed to maximize your mileage.



Features & Benefits

- V-sipes improve traction in wet conditions and dissipate heat for prolonged tread life.
- Main groove stone ejectors protect tire against stone drilling.
- 5 full depth grooves for excellent traction in wet and dry conditions.
- Decoupling grooves help minimize irregular wear.



Applications:

- Free-Rolling Wheel Positions
- Trailers
- Tag Axles

